



XX=No. of contacts

REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	2016-4-25

备注:

1. 性能:

- 额定电压: 250V
- 额定电流: 3AMP
- 接触阻抗: 30mΩ MAX.
- 绝缘阻抗: 1000MΩ MIN. at 500V DC
- 耐电压: 500V Per minute
- 温度范围: -55° C~105° C

2. 材质:

- 胶芯: PBT+30% G. F(UL94V-0) 黑色
- 端子: H62(C2800), 镀镍底30u" Min. 接触部镀金0.8u"Min. 焊接部镀亮锡80u" Min.
- 铁壳: SPCC, 前壳镀铜底50u' 镍80u"Min. 后壳镀铜底50u". 镀全亮锡100u"Min.

ANYCONN® 东莞市恩康电子有限公司

www.enkcom.com **DONGGUAN ANYCONN ELECTRONICS CO.,LTD**

TOLERANCE	PROJECTON		TITLE:			
ANGLE ±5°	DATE :	2016-4-25	HDB 26M 黑色传统焊线			
X.XXX ±0.10	DRAWN :	zhang	PART NO:			
X.XX ±0.20	CHECKED :		DRAWING NO:			
X.X ±0.30	APPROVED :		REV:	UNIT:	SCALE:	SIZE:
X. ±0.50			A0	mm	1:1	A4